

3-Person Hands-Free Wall Mount Stainless Steel Wash Station

Model	Flow-Rate
56W1	Standard 2.0 GPM
56W1-0.5	Low-Flow 0.5 GPM

Product Specifications

Constructed from welded #16 gauge type 304 stainless steel. The front, bottom and back are formed from a single sheet with a rolled rim on front and sides. Exposed surfaces have a blended uniform satin finish. Specially designed knee valves provide easy access to working parts without disconnecting mount or plumbing.

Outside Dimensions	60" x 20" x 18" High
Inside Bowl Size	57" x 16-1/2" x 8" Deep
Back Splash Height	10"
Water Activation	Single Knee Pedal Valve
Flow Rate	2 GPM
Inlet Connections	3/8" Male Compression
Drain Opening	2"
Finish	Satin
Strainer	1-1/2" Dia. Duo Basket Strainer
Wall Mounting Bracket	1/4" Dia. Mounting Holes

Includes

- (1) Wall mount wash station
- (3) Single knee pedal valve with 4 nuts
- (3) Swivel gooseneck spout with aerator
- (3) Connecting tube for valve to spout connection
- (6) Fittings, brass, 0.375" male compression and 0.375" male NPT
- (3) Mixing check valve
- (2) Wall-mounting brackets
- (2) Support brackets
- (1) Strainer assembly with basket

Product Compliance

NSF/ANSI 2 Food Equipment
NSF/ANSI 372 Low-Lead



Part: _____ Quantity: _____

Project: _____

Contact: _____

Date: _____

Approval: _____

Notes:



WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

COLUMBIA PRODUCTS
800.626.2117 • columbiasinks.com • info@columbiasinks.com

©2021 Columbia Products

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall Dimensions:**
 - Length: 60" (1524mm)
 - Width: 20" (508mm)
- Internal Dimensions and Features:**
 - Top edge: 30" (762mm) from left to center, 30" (762mm) from center to right.
 - Right edge: 2" (51mm) from top to center, 16.5" (407mm) from center to bottom.
 - Bottom edge: 1.5" (38mm) from left to center, 57" (1448mm) from center to right.
 - Left edge: 10.25" (267mm) from top to center.
 - Center: 2" drain hole.
 - Corner: .5" R (12.7mm) radius.

Front

Diagram showing the front view of the workstation with dimensions and labels:

- Overall width: 49.5" (1,257.3mm)
- Overall height: 10" (254mm)
- Top panel thickness: .75" (19mm) slot
- Top panel radius: .5" R (12.7mm)
- Wall-mounting brackets (indicated by dashed lines)
- Bottom panel height: 8" (203mm)
- Bottom panel thickness: .437" (6mm) dia. hole
- Bottom panel height (from top of bottom panel to top of base): 4" (101.6mm)
- Base height: 4" (101.6mm)

Side

20" (508mm)

2" (51mm)

7.5" (191mm)

1.5" (38mm)

35" (889mm)
suggested
floor to rim
height

16.75" (425.5mm)

45°

Supply Line to Spout

[illegible]

Technical drawing of the back splash assembly showing dimensions: 2" (51mm) height, .375" dia. hole, and .875" (22.22mm) height. The drawing is labeled "Back Splash".

Back Splash

3/8" Male Compression

Supply Line from Valve to Spout

